


Bridgehill Pallet Truck / Forklift Standard Fire Blanket



Controls fire in forklifts and pallet trucks within seconds

Product Overview

The most efficient way to isolate and extinguish a fire in forklifts and pallet trucks, even isolate fire in electric forklifts.



Fire is one of the most common causes of damage and downtime in factories, warehouses, and other workplaces. The smoke alone can ruin valuable stock and equipment. If a fire is not isolated quickly, the consequences can be disastrous. The Bridgehill Forklift Fire Blanket enables you to isolate the flames, smoke, and toxic fumes in seconds – and extinguish the fire in minutes. It works effectively on forklifts, small vehicles, and machinery, and is the only solution to also work on vehicles with lithium batteries.

- Controls fire in forklifts within seconds
- The most efficient solution for isolating fire in forklifts, even electric battery powered
- Immediately isolates toxic gases and smoke, protecting civilians from carcinogen exposure
- Protecting the goods and buildings from fire, reducing down time
- Delivered in a smartbag
- EN 13501-1: Reaction to fire classification A1
- EN ISO 1716: Determination of the gross heat of combustion
- EN ISO 1182: Non-combustibility test

Ideal for: Warehouses – Ports – Factories – Manufacturing companies and other places where it is critical to control fire quickly

Size / Weight

Pallet truck: $\pm 5 \times 5 \text{ m} \pm 15 \text{ kg}$

Forklift standard: $\pm 7 \times 7 \text{ m} \pm 30 \text{ kg}$

How To Use

Handled by two people

1. Place the fire blanket on the ground in front or behind the forklift and roll it out.
2. Two people should grab each their handle and safely pull the fire blanket over the forklift in one continuous movement.
3. On forklifts with a tall mast, cover the cabin not the mast.
4. Make sure the fire blanket is tight all the way to the ground and leave the fire blanket on for minimum 20 minutes. Wait for firefighters to assess the situation further.

ALWAYS CALL THE FIRE DEPARTMENT

Fire in electric forklifts: In many cases you might hear a strong fuzzing sound, which indicates a thermal runaway. We recommend to leave the fire blanket on until the vehicle has been transported to a safe place and assessed by professionals.

Remember that a battery might reignite at any time.



Bridgehill Pallet Truck / Forklift Standard Fire Blanket



Controls fire in forklifts and pallet trucks within seconds

Pallet Truck / Forklift Standard First Responder	
SKU	Pallet Truck: 211227 Forklift Standard: 201252
Size/Weight	Pallet Truck: $\pm 5 \times 5 \text{ m}$ (25 m ²) / $\pm 15 \text{ kg}$ Forklift Standard: $\pm 7 \times 7 \text{ m}$ (49 m ²) / $\pm 30 \text{ kg}$
Core Material	380 gsm pyroxene
Coating	± 120 silicone polymer (flames may occur during first time use). In fires with high levels of conduction heat, flames may appear from the coating of the fire blanket. This will not alter the performance of the fire blanket
Main usage	<ul style="list-style-type: none">Fossil fuel forkliftsElectric forklifts (isolating the fire in the battery)
Smartbag	Airtight bag. Smartbag care and maintenance: Use silicon grease on the zipper to keep the bag airtight and smell free.

Core Fabric			Unit	Tolerance
Yarn	Warp Weft	300 165	Tex Tex	± 5
Yarn Count	Warp Weft	8 8	Ends/cm Ends/cm	± 5
Tensile Strength	Warp Weft	3200 2500	N/50mm N/50mm	\geq
Thickness	-	0.4	mm	$\pm 5\%$
Weave Pattern	-	Plain	-	-
Service Temperatures on Core Fabric	Short term $\pm 1600 \text{ }^{\circ}\text{C}$ Long term $\pm 800 \text{ }^{\circ}\text{C}$			

Warning

Avoid inhaling smoke from the burning object. Do not put yourself at unnecessary risk, call the fire department!

In fires with high levels of conduction heat, flames may appear from the coating of the blanket. This will not alter the purpose of the blanket.

Pallet truck: $\pm 5 \times 5 \text{ m}$



Forklift standard: $\pm 7 \times 7 \text{ m}$

