

# CleanSpace™

## CST PRO Power System

CST1000 | Built for Everyday Environments

**CleanSpace®**  
RESPIRATORS  
Free the way you breathe™

### Product Overview

A CleanSpace CST PRO Power System consists of the following listed items:

- CST1002 CleanSpace™ CST PRO Power Unit
- CST1019/CST1020 CleanSpace CST Neck Supports
- PAF-1101 Battery Charger, All Models
- One Carry Bag
- Quick Start Guide

Note: The CleanSpace CST PRO Power System does not include a filter or mask.

### Key Features

- Patented AirSensit® technology is breath responsive, adjusting to your breathing requirements for optimal comfort and performance
- Compact and lightweight: (< 500g) - easy to don and doff
- Improved mobility with no belts or hoses allowing you to work more freely
- Connected via Bluetooth to the CleanSpace SMART App
- Battery run time up to 14 hours\*; fast recharge
- Compatible for use with with CST particulate and particulate/chemical filters, providing 99.97% filtration efficiency
- Certified for use with Half Mask and Full Face Mask

\*Operating time is strongly affected by filter type, filter loading, mask seal, work rate, altitude, and other factors. The operating times quoted above are average durations at moderate work rates at sea level. Actual operating times may vary widely from the quoted average durations.



[www.frsa.com.au](http://www.frsa.com.au) | [admin@frsa.com.au](mailto:admin@frsa.com.au) | + 61 7 3209 7422

## Product Overview

The CleanSpace CST PRO offers you the ultimate protection that is both durable and lightweight, making it perfect for use during more challenging tasks.

The CleanSpace PRO Power Unit is a powered air purifying respirator (PAPR) when worn together with the following compatible items:

- A CleanSpace CST Full Face Mask (CST1017, CST1018), OR
- A CleanSpace CST Half Mask and Head Harness (CST1034, CST1035, CST1036), and
- A range of CleanSpace CST particulate and gas/vapour filters.

Suitable for use in environments which require respiratory protection against airborne biohazards, particulates, dust, gas and vapours.

This device is Bluetooth™ enabled and able to connect to the CleanSpace Smart App.

## Key Features

- Lightweight, compact and comfortable
- One power button for simple operation
- AirSensit™ Technology:
  - Mask pressure control and breath responsive airflow
  - filter life management
  - battery life management
- Intelligent Management Filter Technology (IMFT): filter life optimization and real-time insights
- Mask-release and adjust buttons suitable for gloved hands
- Long run time and short battery recharge time
- Compatible with CleanSpace Smart App (available at Google Play and Apple App stores)

## Specifications

- Weight: 415 g
- Dimensions: 210 mm x 180 mm x 70 mm
- Peak Airflow: 230 l/min
- Battery: Lithium-ion polymer
- Operating Time: up to 14 hrs
- Battery recharge time: < 2 hrs
- AC Adaptor Charger: Input 100 – 240V, 50 to 60Hz, output 14.7Vdc ±5%, 24W



## Approvals

- Standard: EN12942:1998+A2:2008; AS/NZS 1716: 2012
- Classification: TM3; PAPR-P3 (P2 with Half Mask)

---

## Applications

Suitable for environments which require respiratory protection against airborne biohazards, particulates, dust, gas, and vapours.

Examples: Welding, Woodworking, Manufacturing, Smelting, Construction, Transportation, Recycling Plants, Emergency Services, Mining, Agriculture, Processing Plants, Grinding. CleanSpace PRO respirators are NOT suitable for asbestos removal, applications where decontamination showers are used or intrinsically safe certified operations.

## Limitations

CleanSpace respirators are air filtering, fan assisted, positive pressure systems and designed to be worn in environments where there is sufficient oxygen to breathe safely. Do not use CleanSpace respirators in immediately dangerous to life or health (IDLH) atmospheres, to protect against gases/vapours that cannot be filtered or in oxygen enriched or deficient atmospheres.

CleanSpace PRO Power Unit is not water tolerant/IP Rated or not certified as intrinsically safe.

## Use, Charging & Storage Conditions

- Use temperature range: -10°C to +45°C (14°F to +113°F) at < 90% relative humidity
- Charging temperature range: 0°C to 35°C (32°F to 95°F)
- Storage conditions: +10°C to +30°C (+50°F to +86°F) at < 75% relative humidity

# CleanSpace®

## CST Neck Support

CST1019 (Small), CST1020 (Medium)

**CleanSpace®**  
RESPIRATORS  
Free the way you breathe™

### Product Overview

CleanSpace CST Neck Supports are specifically designed to provide additional positioning options of the power unit for optimal wearer comfort. They are compatible with the CleanSpace PRO Power Unit (CST1002) and CleanSpace ULTRA Power Unit (CST1012).

A CleanSpace CST Neck Support is made of light weight polypropylene plastic. It clips directly into the Power Unit and is easily changed.

A CleanSpace CST Neck Support is NOT certified intrinsically safe.

### Key Features

- Designed for comfort over long periods
- Available in 2 sizes to accommodate different neck sizes
- Allows space between the wearer and the Power Unit for breathability
- The neck support articulates, allowing for full head movement
- Designed for long wear in harsh environments

### Applications

Examples: Mining, Welding, Manufacturing, Smelting, Construction, Recycling Plants, Emergency Service, Agriculture, Processing Plants, Grinding.

The CleanSpace ULTRA system (CST1010) fitted with a CleanSpace CST Neck Support is suitable for chemical applications where decontamination showers are used.

### Specifications

- Product Weight: CST 1019: 9 g, CST1020: 8 g
- Materials: Polypropylene plastic

### Limitations

CleanSpace respirators are air filtering, fan assisted, positive pressure systems and designed to be worn in environments where there is sufficient oxygen to breathe safely. Do not use CleanSpace respirators in immediately dangerous to life or health (IDLH) atmospheres, to protect against gases/vapours that cannot be filtered or in oxygen enriched or deficient atmospheres.

### Cleaning, Use & Storage Conditions

- Cleaning: Warm water and mild detergent (neutral pH 6 – 8). Do not use solvents (turpentine or acetone), hot water, bleaching or chemical agents
- Use temperature range: -10°C to +45°C (14°F to +113°F) at < 90% relative humidity
- Storage temperature range: +10°C to +30°C (+50°F to +86°F) at < 75% relative humidity
- Store away from direct sunlight, grease and oil



### Approvals

- Standard: EN 12942:1998+A2:2008; AS/NZS 1716: 2012
- Classification: TM3; PAPR-P3

[www.frsa.com.au](http://www.frsa.com.au) | [admin@frsa.com.au](mailto:admin@frsa.com.au) | + 61 7 3209 7422

# CleanSpace®

## Battery Charger (All models)

PAF-1101

**CleanSpace®**  
RESPIRATORS  
Free the way you breathe™

### Product Overview

The CleanSpace Battery Charger is specifically designed to re-charge the internal lithium polymer battery of all CleanSpace Power Units. The battery charger has one lead and interchangeable plugs for use in different countries.

### Key Features

- Used with the revolutionary CleanSpace PAPR: light weight, no hoses or belts
- Multinational interchangeable plugs

### Specifications

- Weight: 210g
- Dimensions: 163mm x 95mm x 70mm
- Cleaning: This part is NOT waterproof. Do not use solvents (turpentine or acetone), hot water, bleaching or chemical agents.
- Storage and Use: -10°C to +45°C (-4°F to +113°F) at <90% relative humidity.
- Store away from direct sunlight, grease and oil

### Limitations

CleanSpace respirators are air filtering, fan assisted, positive pressure systems and designed to be worn in environments where there is sufficient oxygen to breathe safely. Do not use CleanSpace respirators in immediately dangerous to life or health (IDLH) atmospheres, to protect against gases/vapours that cannot be filtered or in oxygen enriched or deficient atmospheres.

### Approvals

- Standard: AS/NZS1716: 2012; EN 12942
- Classification: PAPR-P3

