

holmatro

mastering power

PRODUCT data sheet

HSB27 Stack Bag

Specifications

opeeniduuono	1	
article number		350.321.033
model		HLB 96
short description		Lifting Bag
max. working pressure	bar	12
max. inflation height	mm	565
thickness incl. profile	mm	27
max. lifting capacity	kN/t	940 / 95.9
max. lifting capacity (12 bar/174 psi)	kN/t	940 / 95.9
max. lifting capacity (8 bar/116 psi)	kN/t	627 / 63.9
air content (12 bar/174 psi)	I	1619
air content (8 bar/116 psi)		1079
water content	I	135
connection		ISO 6150 C
min. bursting pressure	bar/Mpa	48 / 4.8
material		reinforced with 3 aramide inlays
weight, ready for use	kg	25.0
dimensions (AxBxC)	mm	987 x 910 x 27
thread hole	threadsize	M6
temperature range	°C	-20 + 55
EN 13731 compliant		yes

Required Accessories

-	
Control Unit HTC12	151.002.137
Shut-Off Hose SOH 12	350.182.096
Pressure Reducer PRV 12	350.182.100
Air Hose AH 5 Y	350.570.022
Air Hose AH 5 B	350.570.023
Air Hose AH 10 B	350.570.026
Air Hose AH 10 Y	350.570.027
Air Hose AH 5 O	350.570.030
Air Hose AH 10 O	350.570.031
Pressure Reducer PRV 12 CGA346	358.182.000
Pressure Reducer PRV 12 HP	358.182.001
Shut-Off Hose SOH 174	358.570.007
Air Bottle 300 Bar	350.581.096
Air Hose AH 16 Y	358.570.001
Air Hose AH 16 B	358.570.002
Air Hose AH 16 R	358.570.003
Air Hose AH 32 R	358.570.004
Air Hose AH 32 B	358.570.005
Air Hose AH 32 Y	358.570.006

Standard Supplied With

Carrying strapsFlexible integrated dust cap on air inlet













