

PRODUCT DATA SHEET

PRA40 RAM

Specifications

article number		151.002.436
model		PRA40
short description		Ram
max. working pressure	bar/Mpa	540 / 54
battery included		no
spreading stroke	mm	215
retracted length	mm	385
extended length	mm	600
spreading force over full stroke	kN/t	136 / 13.9
protection rate		IP57
sound emission @ 1m/3.25ft	dB(A)	75
sound emission @ 4m/13ft	dB(A)	66
hydraulic oil type		ISO-L HV VG 36
number of plungers		1
weight, ready for use	kg	14.2
temperature range	°C	-20 +55
weight excl. battery	kg	12.6
dimensions (AxBxC)	mm	385 x 256 x 443
EN 13204 classification		R136/215-14.2
EN 13204 compliant		yes
NFPA 1960, HSF	kN/t	136 / 13.9
NFPA 1960, LSF	kN/t	136 / 13.9
NFPA 1960 compliant		yes
prEN 13204 classification		F-RA-136/215

Safety Factors / Tests

hydraulic safety factor	2:1
endurance test tool	1000 cycles of spreading while the tool is loaded
endurance test dead man's handle	6000 cycles

Required Accessories

Battery Charger PBCH1 (AC-EU)	151.000.629
Battery Charger PBCH4 (AC-JP)	151.000.630
Battery Charger PBCH5 (AC-UK)	151.000.631
Battery Charger PBCH3 (DC)	151.000.632
Battery Charger PBCH2 (AC-US)	151.000.742
Battery Charger PBCH6 (AC-KR)	151.001.209
Battery Charger PBCH7 (AC-CN)	151.001.518
Battery Charger PBCH8 (AC-IN)	151.001.519
Battery PBPA288	151.004.315
Battery PBPA288 (CN)	151.004.434



