

PRODUCT DATA SHEET

PTR40 TELESCOPIC RAM

Specifications

article number		151.002.438
model		PTR40
short description		Telescopic Ram
max. working pressure	bar/Mpa	540 / 54
battery included		no
spreading stroke 1st plunger	mm	215
spreading stroke 2nd plunger	mm	192
total spreading stroke	mm	407
retracted length	mm	385
extended length	mm	792
max. spreading force 1st plunger	kN/t	136 / 13.9
max. spreading force 2nd plunger	kN/t	65 / 6.6
protection rate		IP57
sound emission @ 1m/3.25ft	dB(A)	75
sound emission @ 4m/13ft	dB(A)	66
hydraulic oil type		ISO-L HV VG 36
number of plungers		2
weight, ready for use	kg	15.6
temperature range	°C	-20 +55
weight excl. battery	kg	14.0
dimensions (AxBxC)	mm	385 x 256 x 443
EN 13204 classification		TR136/215-65/192-15.6
EN 13204 compliant		yes
NFPA 1960, HSF	kN/t	136 / 13.9
NFPA 1960, LSF	kN/t	65 / 6.6
NFPA 1960 compliant		yes
prEN 13204 classification		F-TR-136/215-65/192

Safety Factors / Tests

hydraulic safety factor	2:1
endurance test tool	1000 cycles of spreading while the tool is loaded
endurance test dead man's handle	6000 cycles

Required Accessories

Battery Charger PBCH1 (AC-EU)	151.000.629
Battery Charger PBCH4 (AC-JP)	151.000.630
Battery Charger PBCH5 (AC-UK)	151.000.631
Battery Charger PBCH3 (DC)	151.000.632
Battery Charger PBCH2 (AC-US)	151.000.742
Battery Charger PBCH6 (AC-KR)	151.001.209
Battery Charger PBCH7 (AC-CN)	151.001.518
Battery Charger PBCH8 (AC-IN)	151.001.519
Battery PBPA288	151.004.315
Battery PBPA288 (CN)	151.004.434



