Holmatro Next-Gen Pentheon Spreader PSP40CL



Unrivaled Performance | Superior Usability

Product Overview

Cordless Spreader, part of the Holmatro Pentheon Series. Designed to offer you unrivaled performance, superior usability, advanced connectivity and exceptional serviceability.

Key Features

- Unparalleled speed for faster rescue operations
- Ultimate speed control for more controlled tool handling
- Guaranteed maximum power during a tool's entire lifespan
- Battery management made easy
- Superb ergonomics for effortless handling
- · Continue your mission under all conditions
- · Realtime tool insights to adapt and change tactics
- Automatically keep your tools in perfect condition
- Effortless tool maintenance
- Phenomenal grip over the full spreading range

Unrivaled Performance

When you explore the power of Pentheon, you will have the fastest and most advanced rescue tools in the world. Whether you need speed, precision or durability, Pentheon always delivers an extraordinary level of performance. Enabling you in making every rescue operation successful.

Superior Usability

Combining flawless performance with first-class handling has always been one of Pentheon's main goals. The tools must be an extension of you, the first responder. Holmatro's next-gen Series forms no exception to this mission. No matter the challenge, Pentheon's ergonomic design gives you the upper hand in taking it on effortlessly.

Advanced Connectivity

Holmatro leads the way in implementing technological innovations. With the undeniable importance of smart products and connectedness in mind, the next-gen Pentheon Series is packed with connectivity features such as Bluetooth® and a dedicated app.

Exceptional Serviceability

An unmatched uptime is one of the key elements in experiencing unrestrained performance for every mission. To ensure that you can keep on going, we offer the highest level of serviceability on the market. And if you or your asset manager can't perform a tune-up, our technicians most certainly can.

www.frsa.com.au | admin@frsa.com.au | + 61 7 3209 7422



Holmatro Next-Gen Pentheon Spreader PSP40CL Unrivaled Performance | Superior Usability



| Specifications | | |
|---|---------|-----------------|
| Article number | | 151.002.431 |
| Model | | PSP40CL |
| Short description | | Spreader |
| Max. working pressure | bar/Mpa | 720 / 72 |
| Battery included | | No |
| Connectivity, mobile app | | Bluetooth |
| Spreading distance | mm | 510 |
| Max. pulling force | kN/t | 48 / 4.9 |
| Pulling distance | mm | 393 |
| Max. spreading force | kN/t | 131 / 13.4 |
| Theoretical calculated spreading force | kN/t | 875 / 89.2 |
| Min. spreading force (EN 13204) | kN/t | 43 / 4.4 |
| Max. spreading force, 25mm/1in from the tip | kN/t | 70 / 7.1 |
| Max. squeezing force | kN/t | 47 / 4.8 |
| Sound emission @ 1m/3.25ft | dB(A) | 74 |
| Sound emission @ 4m/13ft | dB(A) | 65 |
| Hydraulic oil type | | ISO-L HV VG 36 |
| Weight (excl. battery) | kg | 13.7 |
| Temperature range | °C | -20 +55 |
| Dimensions (AxBxC) | mm | 811 x 270 x 276 |
| Weight, ready for use (incl. battery) | kg | 15.3 |
| EN 13204 compliant | | Yes |
| prEN 13204 classification | | F-SP2-43/510 |
| NFPA 1960, HPF | kN/t | 48 / 4.9 |
| NFPA 1960, HSF | kN/t | 53 / 5.4 |
| NFPA 1960, LPF | kN/t | 27 / 2.8 |
| NFPA 1960, LSF | kN/t | 39 / 4 |
| NFPA 1960 compliant | | Yes |





www.frsa.com.au | admin@frsa.com.au | + 61 7 3209 7422



| Safety Factors / Tests | | |
|----------------------------------|--|--|
| Hydraulic safety factor | 2:1 | |
| Endurance test tool | 1000 cycles of opening and closing while arms are loaded | |
| Endurance test dead man's handle | 6000 cycles | |
| Required Accessories | | |
| Battery Charger PBCH1 (AC-EU) | 151.000.629 | |
| Battery Charger PBCH4 (AC-JP) | 151.000.630 | |
| Battery Charger PBCH5 (AC-UK) | 151.000.631 | |
| Battery Charger PBCH3 (DC) | 151.000.632 | |
| Battery Charger PBCH2 (AC-US) | 151.000.742 | |
| Battery Charger PBCH6 (AC-KR) | 151.001.209 | |
| Battery Charger PBCH7 (AC-CN) | 151.001.518 | |
| Battery Charger PBCH8 (AC-IN) | 151.001.519 | |
| Battery PBPA288 | 151.004.315 | |
| Battery PBPA288 (CN) | 151.004.434 | |



