

# Seek Thermal AttackPRO Kit

Durable, High-Resolution Thermal Imaging Camera



## Product Overview

Designed with firefighters for firefighters, the AttackPRO™ thermal imaging camera offers an unmatched combination of image quality, durability, and price.

With its high resolution and wide field of view, AttackPRO is the new decision-making weapon of choice for captains and commanding officers. Mixed-gain pixel technology eliminates the visual confusion and delay of switching between highgain and low-gain modes. AttackPRO lets you clearly see the fire and the crew, all in one detailed image.

The kit includes the AttackPRO camera, 2 batteries, and a charging dock.

Designed and Manufactured in the USA with Global Components. Thermal sensor designed and manufactured by Seek in Santa Barbara, CA USA

## Key Features

- Mixed Gain with SV1 Image Optimization: See the hottest and coolest regions of the scene simultaneously without freezing or switching gain modes; details enhanced with SV1
- Durable, Waterproof Design: Durable and reliable design built with IP67 rating and 2 meter drop resistance
- Wide, 57-Degree Field of View: Easily scan a large area to identify hazards or victims in seconds
- Long-Lasting Rechargeable Battery: Greater than 6 hours of continuous thermal imaging
- Simple Operation. Purpose-Built for the Fire Ground: One button thermal operation, no confusing menus or settings, Get the job done efficiently and consistently

## Benefits

- Decision Making on Command: direct Firefighters, water, and resources with expedited tactical precision
- Robust Decision Making TIC: equip every commanding officer with the first affordable decision making TIC
- 300 Lumen Integrated Flashlight: LED flashlight available at the touch of a button
- Search and Rescue: find victims and self-rescue faster with a reliable personal TIC
- Execute 360 Size-ups & Overhaul Faster: when seconds count, a Seek decision-making TIC saves time and lives



Key Camera Specs	
Resolution	320 x 240
Field of View	57° x 42°
Durability	IP67 waterproof, 2 meter drop
Detection	-4°F to 1022°F (-20°C to 550°C)
Imaging	Mixed Gain with SV1
Flashlight	300 Lumen LED

www.frssa.com.au | admin@frssa.com.au | + 61 7 3209 7422

# Seek Thermal AttackPRO Kit

Durable, High-Resolution Thermal Imaging Camera



Specifications	Description
Thermal Sensor	320 x 240 (76,800 pixels)
Detection Distance	12 inches to 1,000 feet
Field of View	57° HFOV, 42° VFOV
Temperature Range	-4 to 1,022°F (-20 to 550°C)
Operating Temp	-4 to 131°F (-20 to 55°C) - no time limit up to 302°F (150°C) - max 15 min up to 500°F (260°C) - max 5 min
Frame Rate	> 25 Hz Fast Frame
IP Rating	IP67 Waterproof
Flashlight	300 Lumen LED
Display	3.5" Color with Corning® Gorilla® Glass
Thermal Sensitivity	< 35 mK with SV1
User Interface	On device 2 tactile button operation
Temp. Display Scale	Fahrenheit or Celsius
Image modes	FIRE (TI Basic & TI Basic+)
Storage Media	NA
Battery	>6 Hours Thermal Imaging (w/o flashlight); >3hrs (with thermal AND flashlight)



Seek AttackPRO combines powerful thermal insight and a bright LED flashlight in an intuitive, two button interface.

## User Interface



### TI BASIC


Maintain your situational awareness with a simple and decluttered display showing grayscale and colorised regions



### TI BASIC+

Enhance your tactics with a spot temp readout while still maintaining grayscale and colorised regions

## Thermal Applications



360 Size Up



Fire Attack



Overhaul

www.frsa.com.au | admin@frsa.com.au | + 61 7 3209 7422

# Seek Thermal AttackPRO Kit

Durable, High-Resolution Thermal Imaging Camera



## Desktop Battery Charger

## Battery Li-ion



### Technical Summary

Specifications	Description
AC Input	100-240 VAC 50/60 HZ, 0.5 A
Supply Voltage	5VDC
Power Rating	10W
Environmental	Intended for Indoor Use
Included In The Box	Desktop Charger Cradle Power Supply Including AC Plugs For US, EU, UK

Specifications	Description
Battery Material	Lithium Ion
Nominal Voltage	3.63 V
Nominal Capacity	4900 mAh
Operating Temperature Range	During Discharge: -20°C TO 60°C During Charging: 0°C TO 45°C
Weight	115g
Size	170 X 45 X 43 mm
Compatible With	FQ-PPAX FQ-PPNX FQ-PAVX FQ-PPSX

www.frsa.com.au | admin@frsa.com.au | + 61 7 3209 7422