

Seek Thermal

FirePRO 300

For Improved Situational Awareness and Safety



Product Overview

FirePRO 300 - the best innovation in personal thermal imaging. With FirePRO 300, you can equip every firefighter with an affordable and lightweight thermal camera to enhance situational awareness and improve firefighter safety.

Featuring our high resolution 320 x 240 sensor, FirePRO 300 provides firefighters with the ability to regain orientation in low visibility or blackout conditions. Additionally, Seek's game-changing Mixed Gain technology allows firefighters to see detail in the hottest and coolest regions of the scene at the same time without freezing and switching modes. Investing in a personal thermal imaging camera is an investment in your personal safety. Designed and manufactured in the USA with global components. Thermal sensor designed and manufactured by Seek Thermal in Santa Barbara, CA USA.

Key Features

- Made to endure and designed to be lightweight: Weighs just 325 grams and is IP67 waterproof with 2 meter drop durability
- Mixed Gain with SV1 Image Optimisation: See the hottest and coolest regions of the scene simultaneously without freezing or switching gain modes; details enhanced with SV1
- Fast Frame Rate, High-Resolution Sensor: 320 x 240 sensor size with 76,800 individual temperature pixels refresh 25 times a second
- Up to 6 hours of use on a single charge: Long lasting rechargeable battery ensures FirePRO 300 is always ready
- Ergonomic 90° viewing angle: 90° viewing angle makes pointing the camera as easy as a cell phone

Benefits

- Improve situational awareness: Visualise hazards invisible to the naked eye and navigate safely
- Find your way out in zero visibility conditions: FirePRO 300 is your lifeline to regain orientation and reduce maydays
- Execute the mission faster: Quickly locate victims and hot spots when every second counts
- Reduce the potential for rekindles: Multiple firefighters can use Survey Mode during overhaul
- Redundancy: Serves as a redundant backup to the team's decision making TIC
- Capture Photos and Record Videos: Save thermal photos and videos for education and training

Key Camera Specs	
Resolution	320 x 240
Field of View	42° x 57°
Durability	IP67 waterproof, 2 meter drop
Detection	-20°C to 550°C (-4°F to 1022°F)
Imaging	Mixed Gain with SV1
Flashlight	300 Lumen LED



Seek Thermal FirePRO 300

For Improved Situational Awareness and Safety




Specifications

Thermal Sensor	320 x 240
Field of View	42° x 57°
Germanium Window	Yes
Video Recording	Yes
Image Capture	Yes
Temperature Range	-4° to 1,022°F (-20° to 550°C)
Operating Temp (no limit)	-4° to 185°F (-20° to 85°C)
Operating Temp (5 min)	302°F (150°C)
Operating Temp (1 min)	500°F (260°C)
Frame Rate	> 25 Hz FastFrame
IP Rating	IP67 Waterproof
Impact Resistance	2 metre drop
Flashlight	300 Lumen LED
Display	2.8" TFT 320 x 240 screen resolution
Thermal Sensitivity	< 35 mK with SV1
Viewing Angle	Ergonomic 90° viewing angle
Imaging Modes	FIRE (with TI Basic & TI Basic +) and SURVEY
Size: H x W x D	5.3 x 3 x 1.8 inches (135 x 76 x 46 mm)
Weight	0.7 lbs (325 grams)
Battery Life	6 hours in thermal only 3.5 hours with flashlight on



Imaging Modes



FIRE MODE
Using TI BASIC
(Without Spot Temp)



FIRE MODE
Using TI BASIC+
(With Spot Temp)



SURVEY MODE
With Spot Temp

www.frsa.com.au | admin@frsa.com.au | + 61 7 3209 7422



FRSA
Fire Rescue Safety Australia