

Product Overview

The innovative transport suspension makes it easy to switch between horizontal and vertical positions without having to rehang. Thanks to the integrated tilt function, the position can be flexibly adjusted or fixed in a stable horizontal position. The simple attachment ensures intuitive and safe handling in various areas of application.

Key Features

- Innovative design: suspension system with tilt function for flexible change of position between horizontal and vertical position
- Flexibility: effortless adjustment of the position without repositioning for efficient handling
- Ease of use: Intuitive attachment for safe and quick handling in different areas of application

Applications

- Shaft
- Various
- Rescue

| Specifications           |                                       |
|--------------------------|---------------------------------------|
| Article number           | SAN-9106                              |
| E-class number           | 40-21-08-11                           |
| Customs tariff number    | 63072000                              |
| Net weight               | 1.00 kg                               |
| Colour                   | Black, Grey, Orange                   |
| Fallindicator            | No                                    |
| Edge approved            | No                                    |
| Maximum lifetime         | 15 years                              |
| Minimum tensile strength | 10.00                                 |
| Minimum temperature      | -35 °C                                |
| Maximum temperature      | 60 °C                                 |
| Lanyard type             | Y-Version                             |
| Working load limit in kn | 10 kN                                 |
| Individually tested      | Yes                                   |
| 100% quality control     | Yes                                   |
| Rope length              | 0.89 m                                |
| Length lanyard           | 0.89 m                                |
| Length                   | 0.89 m                                |
| Maximum length           | 89                                    |
| Material                 | Stainless Steel, Polyester, Polyamide |

