

Product Overview

Designed with firefighters for firefighters, the AttackPRO™ VRS is the latest addition to the AttackPRO Series. AttackPRO VRS builds on the unmatched image quality and durability of the original AttackPRO. It now features video recording, a higher temperature range up to 650°C, and includes Survey Mode to enhance size-up and overhaul operations.

With high-resolution, mixed-gain pixel technology, AttackPRO VRS ensures clear visibility of both fire and crew in one detailed image. The kit includes the camera, 2 batteries, and a charging dock. Designed and Manufactured in the USA with Global Components. Thermal sensor designed and manufactured by Seek in Santa Barbara, CA USA.

Key Features

- Video Recording + 1,200°F Detection + Survey Mode: Record up 5 hours of video on AttackPRO’s 32GB internal drive
- Mixed Gain with SV1 Image Optimisation: See the hottest and coolest regions of the scene simultaneously without freezing or switching gain modes; details enhanced with SV1
- Durable, Waterproof Design: Durable and reliable design built with IP67 rating and 2 meter drop resistance
- Wide, 57-Degree Field of View: Easily scan a large area to identify hazards or victims in seconds
- Long-Lasting Rechargeable Battery: Greater than 6 hours of continuous thermal imaging

Benefits

- Decision Making on Command: Direct Firefighters, water, and resources with expedited tactical precision
- Robust Decision Making TIC: Equip every commanding officer with the first affordable decision making TIC
- 300 Lumen Integrated Flashlight: LED flashlight available at the touch of a button
- Search and Rescue: Find victims and self-rescue faster with a reliable personal TIC
- Execute 360 Size-ups & Overhaul Faster: When seconds count, a Seek decision-making TIC saves time and lives



Key Camera Specs	
Resolution	320 x 240
Field of View	57° x 42°
Durability	IP67 waterproof, 2 meter drop
Detection	-4°F to 1200°F (-20°C to 650°C)
Imaging	Mixed Gain with SV1
Flashlight	300 Lumen LED

Seek Thermal AttackPRO VRS

Video Recording | Survey Mode

Seek[®]
thermal

Specifications	
Thermal Sensor	320 x 240 (76,800 pixels)
Detection Distance	12 inches to 1,000 feet
Field of View	57° HFOV, 42° VFOV
Temperature Range	-4 to 1,200°F (-20 to 650°C)
Operating Temp	-4 to 131°F (-20 to 55°C) - no time limit up to 302°F (150°C) - max 15 min up to 500°F (260°C) - max 5 min
Frame Rate	> 25 Hz Fast Frame
IP Rating	IP67 Waterproof
Flashlight	300 Lumen LED
Display	3.5" Color with Corning® Gorilla® Glass
Thermal Sensitivity	< 35 mK with SV1
User Interface	On device 2 tactile button operation
Temp. Display Scale	Fahrenheit or Celsius
Image modes	FIRE (TI Basic & TI Basic+) and SURVEY
Video Recording	5 Hours of video recording (32GB Internal drive)
Storage Media	NA
Battery	>6 Hours Thermal Imaging (w/o flashlight); >3hrs (with thermal AND flashlight)




Seek AttackPRO VRS combines powerful thermal insight and a bright LED flashlight in an intuitive, two button interface.

Modes



TI BASIC

Maintain your situational awareness with a simple and decluttered display showing greyscale and coloured regions



TI BASIC+


Enhance your tactics with a spot temp readout while still maintaining greyscale and coloured regions



SURVEY MODE

Investigative mode with early colorisation at 65C (150F) ideal for size up, smells & bells, and overhaul

Thermal Applications



360 Size Up



Fire Attack



Overhaul

www.frsa.com.au | admin@frsa.com.au | + 61 7 3209 7422