

TFT Hemisphere Portable Monitor

High Flow | Adaptable



Product Overview

HPM132A: Hemisphere Mountable EN Monitor - 65 mm BSPF Swivel inlet, 65 mm BSPM Rigid Outlet

The Hemisphere™ Mountable Monitor provides high-flow water delivery in challenging firefighting environments, reaching up to 500 GPM (2000 LPM). Engineered for adaptability, this monitor features 360-degree rotation, allowing precise targeting in hard-to-reach areas. With multiple mounting options and a lightweight, portable design, the Hemisphere™ monitor is easy to deploy and maneuver, providing reliable water flow control for firefighting operations in confined or elevated spaces for both industrial and municipal departments.

Key Features

- **Flow Capacity:** Delivers up to 500 GPM (2000 LPM), ideal for a range of firefighting applications
- **360° Aiming:** Allows water to be directed precisely, enhancing flexibility in confined spaces
- **Quick-Attach Mounting System:** Securely mounts to various surfaces, with options like I-beam, hitch, and tank lip clamps for versatile use
- **Lightweight Aluminum Construction:** Easy to transport with a built-in carrying handle, ensuring quick setup and deployment
- **Water Pressurized Safety Pins:** Prevents accidental rotation/release during operation, adding safety and control
- **Adjustable Stream Straightener:** Built-in straightener ensures optimized stream reach and minimal turbulence
- **Flow Control:** Quarter-turn ball valve with a locking bail handle for precise flow management and to prevent unintentional discharge
- **Wide Compatibility:** Standard inlet and outlet sizes of 2.5" NH or BSP fittings, with options for Storz and other quick-connect attachments

Specifications	
Weight	22.600 lbs
Colour	Blue
Brand	Hemisphere™
Bundle	Monitor Only
Monitor Type	Mountable
Certifications	EN
Monitor Supply Size	65 mm
Monitor Supply Type	BSP Female
Monitor Supply Style	Rocker
Monitor Supply Swivel	Swivel
Monitor Horizontal Range	360°
Monitor Vertical Range	360°
Monitor Control	Manual
Monitor Supply Inlets	Single
Monitor Outlet Size	65 mm
Monitor Outlet Type	BSP Male

Monitor Outlet Style	Male Threads
Monitor Outlet Swivel	Rigid
Max Flow Rate	2000 LPM
Bundle Stream Straightener	Integrated
Monitor Valve Type	Ball Valve
Safety Features Pressurized	Pins & Locking Valve Handle



www.frsa.com.au | admin@frsa.com.au | + 61 7 3209 7422