



FRSA
Fire Rescue Safety Australia

GRACE
INDUSTRIES, INC.
FireFighter

PRODUCT DATA SHEET

GRACE INDUSTRIES FX5


In-Command® FX is the ultimate tool in Firefighter Automated Accountability. Protecting All Firefighters At All Times

- NO MORE INTERRUPTING fire ground operations for a voice radio PAR check
- NO MORE CHAOS caused by poor radio audio quality and muffled voices
- NO MORE STRUGGLING to discern who is acknowledging your PAR Check
- IMMEDIATELY IDENTIFY who is calling a MAYDAY
- IMMEDIATELY IDENTIFY who has acknowledged the EVAC command
- AUTOMATED ELECTRONIC ROLL CALL and PAR CALL
- Used by ALL FIREFIGHTERS at ALL TIMES and in ALL ENVIRONMENTS

FEATURES

- Intrinsically Safe to UL913, and CSA C22.2, No 157
- Compliant to NFPA 1982, 2013 Edition TIA 13-2 Requirements for RF PASS New Sound Signature
- Bright, Highly Visible LED Status Indicators
- Large Stainless Steel Grip-Clip & D-Ring
- 98+ dBA Sound Pressure Level at 260°C 500°F
- Data-Logging all PASS status changes (On, Off, Alarm, etc)
- Heat Stress Temperature Alarm on all 5 Line Models
- 200 Hours of Battery Life



FX5	Audio Alarm Only
Features	
30 Second Motion Alarm	✓
Manual Panic Button	✓
Very Loud Audible Alarm	✓
Internal Data Logging all Status Changes (on/off/alarm/etc.)	✓
Low Battery Alarm	✓
Temperature Sensing Alarm	✓
Specifications	
NFPA 1982, 2013 Edition TIA 13-2 Compliant	✓
Intrinsically Safe - UL913/CSA C22.2, No 157	✓
98+ dBA Sound Pressure Level at 500°F/260°C	✓
(3) AA Alkaline LR6 - Manufacturer Specific	✓
200 Hours of Battery Life	✓
24-28 Hours of Operation in Alarm	✓